

Donders real-time fMRI ainGain A MATLAB-based solution for real-time decoding and neurofeedback studies




Adnan Niazi1,2, Philip van den Broek2, Stefan Klanke², Markus Barth², Mannes Poel¹, Peter Desain², Marcel van Gerven²

¹Human Media Interaction group, Faculty of EEMCS, University of Twente ²Donders Institute for Brain, Cognition and Behaviour, Radboud University, Nijmegen

Introduction

Functional MRI (fMRI) is a magnetic resonance imaging (MRI)-based neuroimaging technique used to detect brain areas involved in a task, a process or an emotion. However, fMRI has a critical limitation that data analysis can only be carried out after all scans in a scanning session have been acquired. Unlike fMRI, rt-fMRI allows data analysis simultaneously with image acquisition. With real-time fMRI, an experimenter is able to modify stimulus presentation on-the-fly to reflect ongoing brain activity. The kind of brain-state dependent stimulation or neurofeedback is only possible with real-time fMRI.




Donders real-time fMRI


Donders real-time fMRI is set of Open Source MATLABbased software tools to help you design any real-time fMRI decoding or neurofeedback study.

Why use Donders real-time fMRI ?

- Donders real-time fMRI is modular and highly customizable
- All modules are MATLAB-based so an entire study can
- be designed in just one programming language You can jump start your next real-time fMRI study from our ready-made templates




Specifications




Specifications	
Pipeline delay	Scan time + preprocessing delay = 1 TR + 0.2 s
Minimum possible TR	0.8 s
Prospective acquisition correction (PACE)	PACE and MoCo images series available
Support for multi-echo EPI	Work in progress
Retrospective motion correction	Nearest neighbor interpolation Trilinear interpolation B-Spline Interpolation
Slice time correction	- Linear interpolation - Sinc Interpolation (Slow)
Online GLM for nuisance signal removal	Regresses out activations due to DC offsets, linear drifts and translational motion
Spatial smoothing	Gaussian kernel
Feature reduction	- Brain extraction to remove skull voxels or - Grey matter mask to remove all but grey matter voxels

Demos



For decoding visual imagery, subject imagines a letter, in this case D, on the grid and the classifier prediction modulates the feedback seen by the user



Superimposed pictures of a face and place are presented and subjects are asked to attend to one of them. The semantic category of the attended pictures is decoded in real-time and the neurofeedback is provided by enhancing the attended picture.

Limitations of Donders real-time fMRI

The current implementation works only for SIEMENS fMRI scanners

For GE and Philips scanners, only 'Real-time data export' functionality for exporting scans in real time from the scanner will need to be modified/implemented.

www.analyzed4d.com/rtfmri

